

# Series 2000 (Magstripe Terminal) Model t6-2010



This is timeware's most popular terminal, utilising technology that is used by Banks around the world. The magnetic stripe reader is suitable for all office and light manufacturing environments.

Compatible with the following software:

**timeware®  
Small Business Edition**

**timeware®  
Professional Edition**

## Capacity

1000 employee capacity  
3000 archive record capacity

## Communication

Flexitime offers intelligent networking: Employees using the system may check their real-time balances at all designated terminals on the WAN/LAN Network connection: RJ45 (10BaseT)  
Serial connection: RS232 (9600bps)  
Serial modem compatible

## Features

Business in/Business out (available late 2003)  
Status request (available late 2003)  
t-mail messaging  
Utilises timeware® SDK: available free to third-party developers

## Third-party Software Developers...



### What does the SDK do?

The SDK is designed to aid any programmer in creating his/her own application that communicates with a timeware® terminal. Communication to the terminal can be via an RS232 or TCP/IP connection.

## Specifications

### Terminal dimensions:

Width: 292mm  
Length: 178mm  
Depth: 76mm  
Weight: 700g

**Reader type:** Neuron ISO ABA track-2 magnetic stripe (hi-co)

**Encoding method:** ISO track-2 standard (8 digit) & NMD encoded format

**Reader size:** 90mm

### Miscellaneous:

Standard secondary magstripe reader interface  
Interfaces with external barcode wand  
Standard factory bell driver facility

Series 2000/t6-2010